

LG NeON[®]R


LG370Q1C-V5 | LG365Q1C-V5

60

370W | 365W

LG NeON[®]R is powerful solar module that provides world-class performance. A new cell structure that eliminates electrodes on the front maximizes the utilization of light and enhances reliability.

LG NeON[®]R is a result of LG's efforts to increase customer's values beyond efficiency. LG NeON[®]R features enhanced durability, performance under real-world conditions, an enhanced warranty and aesthetic design suitable for roofs.



Feature



Aesthetic Roof

LG NeON[®]R has been designed with aesthetics in mind: the lack of any electrodes on the front creates an improved, modern aesthetic.



Extended Product Warranty

LG has extended the product warranty of the LG NeON[®]R to 25 years which is top level of the industry.



Enhanced Performance Warranty

LG NeON[®]R has an enhanced performance warranty. After 25 years, LG NeON[®]R is guaranteed to perform at minimum 90.8% of initial performance.



More generation per square meter

The LG NeON[®]R has been designed to significantly enhance its output, making it efficient even in limited space.

About LG Electronics

LG Electronics is a global big player, committed to expanding its operations with the solar market. The company first embarked on a solar energy source research program in 1985, supported by LG Group's vast experience in the semi-conductor, LCD, chemistry and materials industries. In 2010, LG Solar successfully released its first MonoX[®] series to the market, which is now available in 32 countries. The NeON[®] (previous MonoX[®] NeON), NeON[®]2, NeON[®]2 BiFacial won the "Intersolar AWARD" in 2013, 2015 and 2016, which demonstrates LG Solar's lead, innovation and commitment to the industry.



LG NeON[®]R

LG370Q1C-V5 | LG365Q1C-V5

General Data

Cell Properties(Material / Type)	Monocrystalline / N-type
Cell Maker	LG
Cell Configuration	60 Cells (6 x 10)
Module Dimensions(L x W x H)	1,700mm x 1,016mm x 40mm
Weight	17.5 kg
Glass(Thickness / Material)	2.8mm / Tempered Glass with AR Coating
Backsheet(Color)	White
Frame(Material)	Anodized Aluminium
Junction Box(Protection Degree)	IP68 with 3 Bypass Diodes
Cables(Length)	1,000mm x 2EA
Connector(Type / Maker)	MC4 / MC

Certifications and Warranty

Certifications	IEC 61215-1/-1-1/2:2016, IEC 61730-1/2:2016
	UL 1703
	ISO 9001, ISO 14001, ISO 50001
	OHSAS 18001
Salt Mist Corrosion Test	IEC 61701:2012 Severity 6
Ammonia Corrosion Test	IEC 62716:2013
Module Fire Performance	Type 1
Fire Rating	Class C (UL 790)
Product Warranty	25 Years
Output Warranty of Pmax	Linear Warranty*

* 1) First year : 98%, 2)After 1st year : 0.3% annual degradation 3) 90.8% for 25years

Temperature Characteristics


NMOT*	[°C]	44 ± 3
Pmax	[%/°C]	-0.30
Voc	[%/°C]	-0.24
Isc	[%/°C]	0.037

* NMOT(Nominal Module Operating Temperature) : Irradiance 800 W/m², Ambient temperature 20 °C, Wind speed 1 m/s, Spectrum AM 1.5

Electrical Properties (NMOT)

Model		LG370Q1C-V5	LG365Q1C-V5
Maximum Power (Pmax)	[W]	279	275
MPP Voltage (Vmpp)	[V]	36.9	36.6
MPP Current (Impp)	[A]	7.55	7.51
Open Circuit Voltage (Voc)	[V]	40.3	40.2
Short Circuit Current (Isc)	[A]	8.71	8.70

I-V Curves



Electrical Properties (STC*)

Model		LG370Q1C-V5	LG365Q1C-V5
Maximum Power (Pmax)	[W]	370	365
MPP Voltage (Vmpp)	[V]	37.0	36.7
MPP Current (Impp)	[A]	10.01	9.95
Open Circuit Voltage (Voc, ±5%)	[V]	42.8	42.8
Short Circuit Current (Isc, ±5%)	[A]	10.82	10.80
Module Efficiency	[%]	21.4	21.1
Power Tolerance	[%]	0 ~ +3	

* STC (Standard Test Condition): Irradiance 1000 W/m², Cell Temperature 25 °C, AM 1.5, Measure Tolerance ± 3%

Operating Conditions


Operating Temperature	[°C]	-40 ~ +90
Maximum System Voltage	[V]	1,000
Maximum Series Fuse Rating	[A]	20
Mechanical Test Load(Front)	[Pa / psf]	5,400 / 113
Mechanical Test Load(Rear)	[Pa / psf]	4,000 / 83.5

* Test Load = Design x Safety Factor(1.5)

Packaging Configuration

Number of Modules Per Pallet	[EA]	25
Number of Modules Per 40ft HQ Container	[EA]	650
Packaging Box Dimensions (L x W x H)	[mm]	1,750 x 1,120 x 1,221
Packaging Box Gross Weight	[kg]	473

Dimensions (mm / inch)



LG Electronics Inc.
Solar Business Division
LG Twin Towers, 128 Yeouui-daero, Yeongdeungpo-gu, Seoul
07336, Korea
www.lg-solar.com

Product specifications are subject to change without notice.
DS-V5-60-C-G-F-EN-90314

© 2019 LG Electronics. All rights reserved.

