

6,000W HYBRID INVERTER

MODEL: RS-H6048K



FEATURES

- P65 waterproof and dustproof makes the inverter available for various working conditions.
- Built-in WiFi for mobile monitoring (APP is available).
- Built-in alternative port for generator and emergent load.
- Optional external CT sensor to guarantee 100% self-consumption.
- Programmable supply priority for PV, Battery or Grid.
- Built-in communication port for BMS (RS485).
- User-adjustable charging current and voltage.
- Parallel operation up to 6 units .

SPECIFICATIONS

Phase	120/240V Split phase, 120V/208V Two-thirds phase
Maximum PV Input Power	7500W
Rated Output Power	6000VA/6000W
Maximum Charging Power	6000W

GRID-TIE OPERATION

PV INPUT(DC)	Maximum DC Voltage	600VDC
	Start-up Voltage/Initial Feeding Voltage	120VDC/160VDC
	MPP Voltage Range	120VDC~550VDC
	"Number of MPP Trackers/ Maximum Input Current"	2/15A
GRID OUTPUT(AC)	Nominal Output Voltage	120VAC(P-N)/208VAC(P-P)/240VAC(P-P)
	Output Voltage Range	105.5-132VAC per phase
	Nominal Output Current	25A per phase
	Power Factor	0.9lag to 0.9lead
EFFICIENCY	Maximum Conversion Efficiency(DC/AC)	96%

OFF-GRID OPERATION

AC INPUT	AC Start-up Voltage/Auto Restart Voltage	85 VAC(per phase)/90 VAC(per phase)
	Acceptable Input Voltage Range	85-140VAC(P-N)(per phase)
	Frequency Range	50Hz/60Hz(Auto sensing)
	Maximum AC Input Current	40A per phase
PV INPUT(DC)	Maximum DC Voltage	600VDC
	MPP Voltage Range	120VDC~550VDC
	Number of MPP Trackers/ Maximum Input Current	2/15A
BATTERY MODE OUTPUT(AC)	Nominal Output Voltage	120VAC(P-N)/208VAC(P-P)/240VAC(P-P)
	Output Waveform	Pure sine wave
	Efficiency(DC to AC)	91%

HYBRID OPERATION

PV INPUT(DC)	Maximum DC Voltage	600VDC
	Start-up Voltage/Initial Feeding Voltage	120VDC/160VDC
	MPP Voltage Range	120VDC~550VDC
	Number of MPP Trackers/ Maximum Input Current	2/15A
GRID OUTPUT(AC)	Nominal Output Voltage	120VAC(P-N)/208VAC(P-P)/240VAC(P-P)
	Output Voltage Range	105.5-132VAC per phase
	Nominal Output Current	25A per phase
AC INPUT	AC Start-up Voltage/Auto Restart Voltage	85 VAC(per phase)/90 VAC(per phase)
	Acceptable Input Voltage Range	85-140VAC(P-N)
	Maximum AC Input Current	40A per phase
BATTERY MODE OUTPUT(AC)	Nominal Output Voltage	120VAC (P-N), 208VAC (P-P), 240VAC(P-P)
	Efficiency(DC to AC)	91%
BATTERY & CHARGER	Nominal DC Voltage Range	40-62VDC
	Maximum Solar Charging Current	120A
	Maximum AC Charging Current	120A
	Maximum Charging Current	120A

GENERAL

PHYSICAL	Dimension, DxWxH(mm)	215.5x515x700
	Net Weight(kgs)	41
INTERFACE	Parallel Function	Yes, 6units
	Communication Port	RS232, RS485, WI-FI, USB
ENVIRONMENT	Operating Temperature	-25°C to 60°C(>45°C derating)
STANDARD	Protection Degree	IP 65
	Safety	UL 1741SAm, CSA 22.2.107.1
	Grid Connection Standard	IEEE 1547.1:2020
	EMC	FCC CRF47 PART15 B