



SolarEdge Commercial Three Phase Inverters for the 208V Grid

for North America

SE43.2K

INVERTERS



Specifically designed to work with power optimizers

- Easy two-person installation – each unit mounted separately, equipped with cables for simple connection between units
- Balance of System and labor reduction compared to using multiple smaller string inverters
- Independent operation of each unit enables higher uptime and easy serviceability
- No wasted ground area: wall/rail mounted, or horizontally mounted under the modules (10° inclination)
- Integrated arc fault protection and rapid shutdown for NEC 2014 and 2017, per article 690.11 and 690.12
- Built-in module-level monitoring with Ethernet or cellular GSM
- Fixed voltage inverter for superior efficiency (97%) and longer strings
- Integrated DC Safety Switch and optional surge protection & DC fuses (plus & minus)
- Built-in RS485 Surge Protection Device, to better withstand lightning events



SolarEdge Commercial Three Phase Inverters for the 208V Grid for North America SE43.2K

SE43.2K		
OUTPUT		
Rated AC Power Output	43200	VA
Maximum AC Power Output	43200	VA
AC Output Line Connections	4-wire WYE (L1-L2-L3-N) plus PE or 3 wire Delta	
AC Output Voltage Minimum-Nominal-Maximum ⁽¹⁾ (L-N)	105-120-132.5	Vac
AC Output Voltage Minimum-Nominal-Maximum ⁽¹⁾ (L-L)	183-208-229	Vac
AC Frequency Min-Nom-Max ⁽¹⁾	59.3 - 60 - 60.5	Hz
Maximum Continuous Output Current (per Phase) @208V	120	A
GFDI Threshold	1	A
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes	
INPUT		
Maximum DC Power (Module STC), Inverter / Unit	58200 / 19400	W
Transformer-less, Ungrounded	Yes	
Maximum Input Voltage DC to Gnd	300	Vdc
Maximum Input Voltage DC+ to DC-	600	Vdc
Nominal Input Voltage DC to Gnd	200	Vdc
Nominal Input Voltage DC+ to DC-	400	Vdc
Maximum Input Current	114	Adc
Maximum Input Short Circuit Current	135	Adc
Reverse-Polarity Protection	Yes	
Ground-Fault Isolation Detection	350kΩ Sensitivity per Unit	
CEC Weighted Efficiency	97	%
Nighttime Power Consumption	< 12	W
ADDITIONAL FEATURES		
Supported Communication Interfaces	RS485, Ethernet, Cellular GSM (optional)	
Rapid Shutdown	NEC2014 and NEC2017 compliant/certified, upon AC Grid Disconnect	
RS485 Surge Protection	Built-in	
DC SAFETY SWITCH		
DC Disconnect	1000V / 3 x 40A	
DC Surge Protection	Optional, Type II, field replaceable	
DC Fuses on Plus & Minus	Optional, 30A	
STANDARD COMPLIANCE⁽²⁾		
Safety	UL1741, UL1741 SA, UL1699B, UL1998, CSA 2.22	
Grid Connection Standards	IEEE 1547, Rule 21, Rule 14 (HI)	
Emissions	FCC part15 class A	
INSTALLATION SPECIFICATIONS		
Number of units	3	
AC Output Conduit Size / Max AWG / Max PE AWG	2" / 4/0 / 4	
DC Output Conduit Size / Terminal Block AWG Range / Number of Strings ⁽³⁾	2 x 1.25" / 6-14 / 9 strings	
Dimensions (H x W x D)	Primary Unit: 37 x 12.5 x 10.5 / 940 x 315 x 260; Secondary Unit: 21 x 12.5 x 10.5 / 540 x 315 x 260	in / mm
Weight	Primary Unit: 105.8 / 48; Secondary Unit 99.2 / 45	lb / kg
Operating Temperature Range	-40 to +140 / -40 to +60 ⁽⁴⁾	
Cooling	Fan (user replaceable)	
Noise	< 60	dBA
Protection Rating	NEMA 3R	
Bracket Mounted (Brackets Provided)		

⁽¹⁾ For other regional settings please contact SolarEdge support

⁽²⁾ Pending

⁽³⁾ Single input option per unit (up to 3AWG) available

⁽⁴⁾ For power de-rating information refer to: <https://www.solaredge.com/sites/default/files/se-temperature-derating-note-na.pdf>

